



**ANY JOB.  
ANY SIZE.  
ANY PLACE.**

55 Years of American Ingenuity

**475**

The **475** is an economical machine for the professional contractor or a do-it-yourself rental market. Designed for low maintenance, rugged performance, and high production. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.

- Adaptable fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- Light weight machine
- User friendly electric dashboard
- Clear acrylic safety guard allows for easy inspection
- Durable powder coat finish
- Large 14 amp / 2 stage blower
- Semi pneumatic run flat treaded tires
- Built in tool holder



Backed by a manufacturer's  
**2-YEAR WARRANTY - Made in the U.S.A.**

#### **MATERIAL PRODUCTION RATE**

##### **MATERIAL**

**CELLULOSE**      **2100 (953) \***  
                             **70 Bags per hr.\***

**FIBERGLASS**      **700 (318) \***  
                             **23 Bags per hr.\***

##### **w/single 2-Stage Blower**

\* lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of 3 " (7.6 cm.) hose at 16 ft. (4.8 m.) elevation.

##### **NOTE:**

Manufacturer's product brand, density and variable blowing conditions will affect production rate.



# KRENDL

The Innovator in Insulation Equipment™

Scan to learn more about Krendl Machine

# 475

## • POWER REQUIREMENT •

Double input, 15/15 amps each/120 volt/60 hz  
International - Single input, 16 amp 230 volt/50 hz  
CE/CSA/CUL/UL

## • HOPPER CAPACITY •

14 cu. ft. (.39 m<sup>3</sup>)  
Loading made easy with built in adaptable tray

## • WEIGHT/DIMENSIONS •

360 lbs / 37" W x 31.5" D x 63" H  
163 kg. / 94cm x 80cm x 160cm

## • BLOWER/SIZE •

14 amp/2-stage (120 volt)  
Blower System yields  
140 CFM @ 3 1/2 PSI

## • AIRLOCK •

12" x 10" diameter  
(30.5 cm. x 25.4 cm. diameter)  
3" (7.6 cm.) Outlet




## Electric Dashboard

- LED start & stop buttons • Digital hourmeter
- Digital voltmeter • Variable blower speed control
- Recessed power supply



## Dual Agitators

Designed for Constant Material Flow



## Clear Acrylic Safety Guard

Allows for easy Inspection